



Arborrverk	X (mm)	Y (mm)	Z (mm)	Max load (kg)
Schiess	12 000	4 000	1 600	100 000
Gidding & Lewis	3 600	2 400	1 200	20 000

Fräsverk/fler op.	X (mm)	Y (mm)	Z (mm)	Max load (kg)	Paletter (st)
Sajo	1 250	900	650		5
Zayer	7 500	2 000	1 250		2
Quintax, 5-axlig svarv/fräs	1 250	1 000	900		3
Droop & Rein	2 200	800	1 000 –		
You Ji HMC 1200	1 800	1 500	750	5 000	2

Långhålsbormaskin	Length	Borr Ø	Sup. Ø	Max Fla. Ø	Max Weight (kg)
Rheinstahl Wagner	24 000	60–560	100–1800	2 600	55 000



<b>Svarvar (mm/kg)</b>	<b>Length</b>	<b>Swing Ø</b>	<b>Max svarv Ø</b>	<b>Max load (kg)</b>
VDF	3 000	1 020	1 800	5 000
Okuma	1 470	600	450	–
VDF	3 000	680	480	3 150
<b>Karusellsvarvar</b>	<b>Height</b>	<b>Bord Ø</b>	<b>Max svarv Ø</b>	<b>Max load (kg)</b>
Berthiez	2 680	3 000	6 200	40 000
You Ji (drivna verktyg)	1 200	1 600	2 500 2 800	15 000
Morando	1 200	1 700	3 000	10 000
<b>Fler op / svarv</b>	<b>Length</b>	<b>Swing Ø</b>	<b>Max svarv Ø</b>	<b>Max load (kg)</b>
Mazak Integrex e650	4 064	1 050	1 050	3000



Mätmaskin	X (mm)	Y (mm)	Z (mm)	Max load (kg)
Giddings & Lewis	1 270	2 080	1 107	4 450

CNC 3-koordinatsupplösning: 0,0001 mm. Repeterbarhet: 0,002 mm

## Mätarmar (2)

- Romer-CimCore 5028
- Romer-CimCore 5024

## OFP nivå 3:

- Ultraljud (UT)
- Penetrant (PT)
- Magnetpulver (MT)
- Visuell inspektion (VT)

Kilspårsdragning	Spår Length/Width (mm)	Bord (mm)	Ø (mm)	Max load (kg)
Frömag	750/36	800 x 900	13-500	10 000